
Subject: Reauth woes
Posted by [Phil Aiken](#) on Mon, 16 Oct 2006 13:35:51 GMT
[View Forum Message](#) <> [Reply to Message](#)

> <DIV>Also to maintain an =
>almost=20

>real-time=20
> processing power <FONT=20

> =
>size=3D3D2>throughout.</DIV

Subject: Re: Reauth woes
Posted by [John \[1\]](#) on Mon, 16 Oct 2006 14:21:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

chip Pro card with 20 In/out and Delta 66 w/4 x =
> >A-D, D-As and one SPDIF in/out,=20

Subject: Re: Reauth woes
Posted by [Aaron Allen](#) on Tue, 17 Oct 2006 02:44:56 GMT
[View Forum Message](#) <> [Reply to Message](#)

br />
MARGIN-LEFT: 5px; =3D3D
<>>BORDER-LEFT: #000000 =
=3D
>2px=20
solid;=3D20
> MARGIN-RIGHT: 0px"><&BR>> =
<DIV>"Tom=20
=3D
>Bruhl"=3D20
> <<A=3D3D20
>>=20
href=3D3D3D"<A=3D20
> =20
=
=3D
>href=3D3D'mailto:arpeggio@comcast.net">arpeggio@comcast.net&l=
t;/A'>mailto:a
